

## Oil Plus 2C

Finishing oil for MDF surfaces

Oil Plus 2C is a one-coat, environmentally-friendly finishing oil for interior surfaces, such as MDF. The oil colours, decorates and protects your MDF panels in one single coat in record time!



### PRODUKTOPLYSNINGER

#### › Særlige egenskaber

- One-coat application
- 40 standard Oil Plus 2C colours, which can be mixed with each other
- 0% VOC
- Without water and solvents
- Heat-resistant
- Quick-drying

#### › Tekniske egenskaber

- Physical state: liquid
- Odour: linseed oil
- Density: > 0.9 kg/L
- VOC: 0 g/L

#### › Opbevaring

Produktet kan opbevares i op til 36 måneder under tørre og frostfri forhold og i original emballage.

## OPLYSNINGER OM PÅFØRING

### > Brugsvejledning

Apply only to untreated surfaces or surfaces whose previous finishing coats have been removed.

#### Preparation:

Sand the MDF boards with 80-grit paper and continue with 120-grit paper without applying pressure. This prevents dust from sticking. You may sand with a finer grit after that. The grit size of the sandpaper will determine the gloss level of the finishing. This is specific to these MDF surfaces.

We recommend finishing with 150-grit paper.

Thoroughly clean the surface with a compressed-air gun or a wide, soft paint brush to make it dust-free.

**Never use the Rubio Monocoat Cleaner. Do NOT use a damp cloth. These will cause spots that cannot be repaired.**

#### Mixing:

Mix the Oil Plus 2C with the Rubio Monocoat Accelerator comp. B. Mix well. We recommend regularly stirring the product during the application as well.

#### Application:

Use a 150-diameter eccentric sander with a round blue 150/20 sanding pad. Drench the pad with oil. Start in a corner and apply the oil without applying any pressure. After that, continue to apply small amounts of oil to the already treated area and distribute the product evenly. Finish the entire panel this way. Polish sufficiently. The surface must feel nearly dry to the touch. This action is specific to these MDF surfaces.

Let it dry for 12-24 hours.

### > Cleaning:

- The treated surfaces may be cleaned with the Rubio Monocoat Universal Soap. It is recommended to wait approximately 5 days before the first cleaning.
- The application material may be cleaned with the Rubio Monocoat Cleaner (except for disposable items, sponge, cloth, pad).

### > Maintenance - Renovation:

- As soon as the surface loses its silky appearance, you can apply Rubio Monocoat Refresh Eco. Do not wait until the colour fades.
- If the surface has some mini-scratches, regular maintenance with Rubio Monocoat Refresh Eco is recommended.
- If the surface has a worn area and/or where it needs colour repair, you can best repair it with the originally applied product in the original colour.

## > Tips & tricks

- Application options:
  - With a spray gun to 30 g/m<sup>2</sup> with a low-pressure spray gun and a 1/1.2 mm nozzle. The oil then needs to be polished with a round blue 150/20 sanding pad sponge!
  - With a Rubio Monocoat Standard Sponge (for small surfaces). The oil then needs to be rubbed dry with cloths!
- For more gloss and an even better protection, you can apply one or two coats of Rubio Monocoat Refresh Eco, 24 hours after the application of the Oil Plus 2C.
- The mixture of Oil Plus 2C with the Accelerator can be used for 4 hours.
- Not applicable for counters and floors with this specific MDF material.

## > Bemærkninger

### > Packaging

- Bottles 20 ml, 100 ml and 0.5L
- Cans 1 L and 2.5 L
- Sets (cans) of 350 ml, 1.3 L and 3.5 L



### ADVARSEL



Klude og andre påføringsværktøjer gennemvædet af vores olie kan selvantænde. Efter brug bør de lægges i blød i vand et stykke tid, før de bortskaffes.

## > Forbrug

Approx. 25 m<sup>2</sup>/L

*\* This consumption is purely indicative. Results depend on the type of wood and the preparation. It is always recommended to apply a sample to determine the exact consumption.*

## > Værktøj



Used tools can be cleaned with Rubio Monocoat Cleaner.

Se emballagen og sikkerhedsdatabladet for flere oplysninger.

For at se hele vores produktsortiment til beskyttelse og farvning af træ indendørs og udendørs, gå til [www.rubimonocoat.com/da](http://www.rubimonocoat.com/da), [www.rubimonocoat.DK](http://www.rubimonocoat.DK), <https://service.rubimonocoat.com/da>.

Rubio<sup>®</sup>  
**MONOCOAT**  
MUYLLE  FACON

**Muylle Facon NV**

Ambachtenstraat 58  
8870 Izegem (BELGIE)

Tlf. +32 (0) 51 30 80 54

Fax +32 (0) 51 30 99 78

info@muyllefacon.be

[www.rubimonocoat.com](http://www.rubimonocoat.com)

**ANSVAR:** Det er brugerens ansvar at finde frem til ved testning, om produktet er egnet til det valgte anvendelsesområde. Muylle Facon NV kan aldrig holdes ansvarligt for driftstab. Ovenstående information kan blive genstand for ændringer, som vil blive offentliggjort i de opdaterede versioner af det tekniske datablad. Vi kan ikke holdes ansvarlige for dårlige resultater af årsager, der ikke er relateret til produktets kvalitet. Denne tekniske information er blevet udarbejdet på baggrund af den aktuelt tilgængelige information og viden. De nyeste tekniske datablade kan rekvireres, og er desuden tilgængelige på hjemmesiden. **Dato for teknisk datablad: 08/12/2023.**

**Kontroller sikkerhedsinformation før brug af produktet.**

