TDS PLASTIC PRIMER



DESCRIPTION

Special transparent primer for pre-treatment of plastic surfaces, difficult for painting. It is applied quickly. It offers high coverage and adhesion to all plastic surfaces. Ideal for all plastic parts of the car as well as for garden items such as plastic chairs, pots, etc.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm^3/20°C, ASTM D – 1475)
- VOC content: 688 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
  - Touch (20°C, Humidity<65%): 10-15min
  - Through dry (20°C, Humidity <65%): 1h
  - Maximum hardness: 24h
- Coverage: 2m^2/400ml
- Contents: 400ml

INSTRUCTIONS FOR USE

APPLICATION
Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. Apply the primer in several thin layers. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10-25°C.**

AFTER USE
Spray holding the can inverted for 3''. Clean the caps with solvent.

STORAGE
5°C-35°C. Never leave the product inside a vehicle.

CAP SYSTEM



SMART CAP
- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

SAFETY

Request SDS

There are likely to be declinations in digital performance of shades.

ISSUED DATE: 17/06/2026

VERSION: 02

COSMOS LAC S.A.
PAINT INDUSTRY
©2026
PLITHONOS GEMISTOU 1, KALLITHEA 17671 ATHENS – GREECE
T. +30 210 95 70 222 | E. support@cosmoslac.com | W. www.cosmoslac.com
MADE IN GREECE

CERTIFIED QUALITY SYSTEM **ISO 9001**