

**DESCRIPTION**

Primer for difficult substrates. Provides excellent adhesion and good exterior durability. Suitable for one component (1K) coatings and primer for difficult substrates such as galvanized steel and non-ferrous metals. Can be over painted with any colour.

PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm³/20°C, ASTM D – 1475)
- VOC content: 500 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
 - Touch (20°C, Humidity<65%): 10-15min
 - Through dry (20°C, Humidity <65%): 1h
 - Maximum hardness: 24h
- Coverage: 2m²/400ml
- Gloss: 1-3 GLOSS UNITS/MATT (GLOSS METER 60°ASTM D – 1471)
- Contents: 400ml

INSTRUCTIONS FOR USE**APPLICATION**

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. Apply the primer in several thin layers. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10-25°C.**

AFTER USE

Spray holding the can inverted for 3''. Clean the caps with solvent.

STORAGE

5°C-35°C. Never leave the product inside a vehicle.

CAP SYSTEM**SMART CAP**

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

SAFETY

Request SDS

*Cap indicates the color of the paint

COLOR RANGE

349 WHITE



449 GREY

